



700mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7070L025	700 X 250	1544-1621	33	0.14
7070L029	700 X 290	1323-1389	38	0.17
7070L033	700 X 330	1158-1216	44	0.19
7070L037	700 X 370	1029-1080	49	0.21
7070L041	700 X 410	926-972	54	0.24
7070L045	700 X 450	842-884	60	0.26
7070L049	700 X 490	772-810	65	0.28
7070L053	700 X 530	712-748	71	0.31
7070L057	700 X 570	662-695	76	0.33
7070L061	700 X 610	617-648	82	0.35
7070L065	700 X 650	579-608	87	0.38
7070L069	700 X 690	545-572	92	0.40
7070L073	700 X 730	515-540	98	0.43
7070L077	700 X 770	487-512	103	0.45
7070L081	700 X 810	463-486	109	0.47
7070L085	700 X 850	441-463	114	0.50
7070L089	700 X 890	421-442	120	0.52
7070L093	700 X 930	403-423	125	0.54
7070L097	700 X 970	386-405	131	0.57
7070L101	700 X 1010	370-389	136	0.59
7070L105	700 X 1050	356-374	141	0.61
7070L109	700 X 1090	343-360	147	0.64
7070L113	700 X 1130	331-347	152	0.66
7070L117	700 X 1170	319-335	158	0.69
7070L121	700 X 1210	309-324	163	0.71
7070L125	700 X 1250	299-314	169	0.73
7070L129	700 x 1290	289-304	174	0.76
7070L133	700 x 1330	281-295	180	0.78
7070L137	700 x 1370	272-286	185	0.80
7070L141	700 x 1410	265-278	190	0.83
7070L145	700 x 1450	257-270	196	0.85
7070L149	700 x 1490	250-263	201	0.88
7070L153	700 x 1530	244-256	207	0.90
7070L157	700 x 1570	237-249	212	0.92
7070L161	700 x 1610	232-243	218	0.95
7070L165	700 x 1650	226-237	223	0.97
7070L169	700 x 1690	221-232	228	0.99
7070L173	700 x 1730	215-226	234	1.02
7070L177	700 x 1770	210-221	239	1.04
7070L181	700 x 1810	206-216	245	1.06

700mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7070L185	700 X 1850	201-211	250	1.09
7070L189	700 X 1890	197-207	256	1.11
7070L193	700 X 1930	193-203	261	1.14
7070L197	700 X 1970	189-198	267	1.16
7070L201	700 X 2010	185-194	272	1.18
7070L205	700 X 2050	182-191	277	1.21
7070L209	700 X 2090	178-187	283	1.23
7070L213	700 X 2130	175-183	288	1.25
7070L217	700 X 2170	172-180	294	1.28
7070L221	700 X 2210	168-177	299	1.30
7070L225	700 X 2250	165-174	305	1.32
7070L229	700 X 2290	162-171	310	1.35
7070L233	700 X 2330	160-168	316	1.37
7070L237	700 X 2370	157-165	321	1.40
7070L241	700 X 2410	154-162	326	1.42
7070L245	700 X 2450	152-159	332	1.44
7070L249	700 X 2490	149-157	337	1.47

Specification:

Approved to: EN60335-1:7002+A1, A2, A11, A12, A13, A14, A15 and EN60335-2-30:7009+A11

Power Rating: 700W/m² | **Standard Voltage:** 230V

Insulation Class: 2-double insulated | **Thickness:** 1 mm

IP Rating: 44

Warranty: Lifetime warranty

Cable connector: 30 x 40 x 5mm | **Cable:** 1m twin core 0.75mm² oval

Adhesive: Acrylic | **Material:** Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 15°C above ambient room temperature

Heating time: 3-5 Minutes depending on ambient room temperature

Heat spread: Approximately 30% area around the pad



Over 700 different sizes available including 12V SELV, 24V and 110V versions

Call our technical support team on 01444 247060 for further information or installation advice:

tech@heatmat.co.uk | www.heatmat.co.uk