



## 600mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7060L025	600 X 250	1810-1900	28	0.12
7060L029	600 X 290	1551-1629	32	0.14
7060L033	600 X 330	1357-1425	37	0.16
7060L037	600 X 370	1206-1267	42	0.18
7060L041	600 X 410	1086-1140	46	0.20
7060L045	600 X 450	987-1036	51	0.22
7060L049	600 X 490	905-950	56	0.24
7060L053	600 X 530	835-877	60	0.26
7060L057	600 X 570	776-814	65	0.28
7060L061	600 X 610	724-760	70	0.30
7060L065	600 X 650	679-713	74	0.32
7060L069	600 X 690	639-671	79	0.34
7060L073	600 X 730	603-633	84	0.36
7060L077	600 X 770	571-600	88	0.38
7060L081	600 X 810	543-570	93	0.40
7060L085	600 X 850	517-543	97	0.42
7060L089	600 X 890	494-518	102	0.44
7060L093	600 X 930	472-496	107	0.46
7060L097	600 X 970	452-475	111	0.48
7060L101	600 X 1010	434-456	116	0.50
7060L105	600 X 1050	418-438	121	0.52
7060L109	600 X 1090	402-422	125	0.54
7060L113	600 X 1130	388-407	130	0.56
7060L117	600 X 1170	374-393	135	0.59
7060L121	600 X 1210	362-380	139	0.61
7060L125	600 X 1250	350-368	144	0.63
7060L129	600 x 1290	339-356	148	0.65
7060L133	600 x 1330	329-345	153	0.67
7060L137	600 x 1370	319-335	158	0.69
7060L141	600 x 1410	310-326	162	0.71
7060L145	600 x 1450	302-317	167	0.73
7060L149	600 x 1490	293-308	172	0.75
7060L153	600 x 1530	286-300	176	0.77
7060L157	600 x 1570	278-292	181	0.79
7060L161	600 x 1610	271-285	186	0.81
7060L165	600 x 1650	265-278	190	0.83
7060L169	600 x 1690	259-271	195	0.85
7060L173	600 x 1730	253-265	200	0.87
7060L177	600 x 1770	247-259	204	0.89
7060L181	600 x 1810	241-253	209	0.91



## 600mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7060L185	600 X 1850	236-248	213	0.93
7060L189	600 X 1890	231-243	218	0.95
7060L193	600 X 1930	226-238	223	0.97
7060L197	600 X 1970	222-233	227	0.99
7060L201	600 X 2010	217-228	232	1.01
7060L205	600 X 2050	213-224	237	1.03
7060L209	600 X 2090	209-219	241	1.05
7060L213	600 X 2130	205-215	246	1.07
7060L217	600 X 2170	201-211	251	1.09
7060L221	600 X 2210	197-207	255	1.11
7060L225	600 X 2250	194-204	260	1.13
7060L229	600 X 2290	190-200	264	1.15
7060L233	600 X 2330	187-197	269	1.17
7060L237	600 X 2370	184-193	274	1.19
7060L241	600 X 2410	181-190	278	1.21
7060L245	600 X 2450	178-187	283	1.23
7060L249	600 X 2490	175-184	288	1.25

### Specification:

**Approved to:** EN60335-1:6002+A1, A2, A11, A12, A13, A14, A15 and EN60335-2-30:6009+A11

**Power Rating:** 600W/m<sup>2</sup> | **Standard Voltage:** 230V

**Insulation Class:** 2-double insulated | **Thickness:** 1 mm

**IP Rating:** 44

**Warranty:** Lifetime warranty

**Cable connector:** 30 x 40 x 5mm | **Cable:** 1m twin core 0.75mm<sup>2</sup> oval

**Adhesive:** Acrylic | **Material:** Double insulated multi-layer polyester/polyethylene

**Mirror temperature:** Approximately 15°C above ambient room temperature

**Heating time:** 3-5 Minutes depending on ambient room temperature

**Heat spread:** Approximately 30% area around the pad



Over 600 different sizes available including 12V SELV, 24V and 110V versions

Call our technical support team on 01444 247060 for further information or installation advice:

[tech@heatmat.co.uk](mailto:tech@heatmat.co.uk) | [www.heatmat.co.uk](http://www.heatmat.co.uk)