



150mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7015L025	150 X 250	8074 – 9420	6	0.03
7015L029	150 X 290	6920 – 7266	7	0.03
7015L033	150 X 330	6055 – 6358	8	0.04
7015L037	150 X 370	5383 – 5652	9	0.04
7015L041	150 X 410	4844 – 5087	10	0.05
7015L045	150 X 450	4404 – 5138	11	0.05
7015L049	150 X 490	4037 – 4239	12	0.05
7015L053	150 X 530	3726 – 3913	14	0.06
7015L057	150 X 570	3460 – 4037	15	0.06
7015L061	150 X 610	3230 – 3391	16	0.07
7015L065	150 X 650	3028 – 3179	17	0.07
7015L069	150 X 690	2850 – 3325	18	0.08
7015L073	150 X 730	2691 – 2826	19	0.08
7015L077	150 X 770	2550 – 2677	20	0.09
7015L081	150 X 810	2422 – 2826	21	0.09
7015L085	150 X 850	2307 – 2422	22	0.09
7015L089	150 X 890	2202 – 2569	23	0.10
7015L093	150 X 930	2106 – 2212	24	0.10
7015L097	150 X 970	2018 – 2355	25	0.11
7015L101	150 X 1010	1938 – 2035	26	0.11
7015L105	150 X 1050	1863 – 2174	27	0.12
7015L109	150 X 1090	1794 – 1884	28	0.12
7015L113	150 X 1130	1730 – 1817	29	0.13
7015L117	150 X 1170	1670 – 1949	30	0.13
7015L121	150 X 1210	1615 – 1696	31	0.14
7015L125	150 X 1250	1563 – 1641	32	0.14
7015L129	150 x 1290	1514 – 1766	33	0.14
7015L133	150 x 1330	1468 – 1541	34	0.15
7015L137	150 x 1370	1384 – 1453	35	0.15
7015L141	150 x 1410	1384 – 1453	36	0.16
7015L145	150 x 1450	1346 – 1413	37	0.16
7015L149	150 x 1490	1309 – 1527	38	0.17
7015L153	150 x 1530	1275 – 1339	40	0.17
7015L157	150 x 1570	1242 – 1304	41	0.18
7015L161	150 x 1610	1211 – 1304	42	0.18
7015L165	150 x 1650	1182 – 1241	43	0.19
7015L169	150 x 1690	1153 – 1211	44	0.19
7015L173	150 x 1730	1127 – 1183	45	0.19
7015L177	150 x 1770	1101 – 1156	46	0.20
7015L181	150 x 1810	1077 – 1256	47	0.20

150mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7020L185	150 X 1850	1053 – 1106	48	0.21
7020L189	150 X 1890	1031 – 1202	49	0.21
7020L193	150 X 1930	1009 – 1060	50	0.22
7020L197	150 X 1970	989 – 1038	51	0.22
7020L201	150 X 2010	969 – 1130	52	0.23
7020L205	150 X 2050	950 – 997	53	0.23
7020L209	150 X 2090	932 – 1087	54	0.24
7020L213	150 X 2130	914 – 960	55	0.24
7020L217	150 X 2170	897 – 942	56	0.24
7020L221	150 X 2210	881 – 1028	57	0.25
7020L225	150 X 2250	865 – 908	58	0.25
7020L229	150 X 2290	850 – 992	59	0.26
7020L233	150 X 2330	835 – 877	60	0.26
7020L237	150 X 2370	821 – 862	61	0.27
7020L241	150 X 2410	807 – 942	62	0.27
7020L245	150 X 2450	794 – 834	63	0.28
7020L249	150 X 2490	781 – 912	64	0.28

Specification:

Approved to: EN60335-1:1502+A1, A2, A11, A12, A13, A14, A15 and EN60335-2-30:1509+A11

Power Rating: 150W/m² | **Standard Voltage:** 230V

Insulation Class: 2-double insulated | **Thickness:** 1 mm

IP Rating: 44

Warranty: Lifetime warranty

Cable connector: 30 x 40 x 5mm | **Cable:** 1m twin core 0.75mm² oval

Adhesive: Acrylic | **Material:** Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 15°C above ambient room temperature

Heating time: 3-5 Minutes depending on ambient room temperature

Heat spread: Approximately 30% area around the pad



Over 400 different sizes available including 12V SELV, 24V and 110V versions

Call our technical support team on 01444 247020 for further information or installation advice:

tech@heatmat.co.uk | www.heatmat.co.uk