



200mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7020L025	200 X 250	5831 – 6123	9	0.04
7020L029	200 X 290	4998 – 5248	10	0.04
7020L033	200 X 330	4373 – 4592	12	0.05
7020L037	200 X 370	3887 – 4082	13	0.06
7020L041	200 X 410	3499 – 3674	14	0.06
7020L045	200 X 450	3181 – 3340	16	0.07
7020L049	200 X 490	2916 – 3061	17	0.08
7020L053	200 X 530	2691 – 2826	19	0.08
7020L057	200 X 570	2499 – 2624	20	0.09
7020L061	200 X 610	2332 – 2449	22	0.09
7020L065	200 X 650	2187 – 2296	23	0.10
7020L069	200 X 690	2058 – 2161	24	0.11
7020L073	200 X 730	1944 – 2041	26	0.11
7020L077	200 X 770	1841 – 1933	27	0.12
7020L081	200 X 810	1749 – 1837	29	0.13
7020L085	200 X 850	1666 – 1749	30	0.13
7020L089	200 X 890	1590 – 1670	32	0.14
7020L093	200 X 930	1521 – 1597	33	0.14
7020L097	200 X 970	1458 – 1531	35	0.15
7020L101	200 X 1010	1399 – 1469	36	0.16
7020L105	200 X 1050	1346 – 1413	37	0.16
7020L109	200 X 1090	1296 – 1361	39	0.17
7020L113	200 X 1130	1250 – 1312	40	0.18
7020L117	200 X 1170	1206 – 1267	42	0.18
7020L121	200 X 1210	1166 – 1225	43	0.19
7020L125	200 X 1250	1129 – 1185	45	0.19
7020L129	200 x 1290	1093 – 1148	46	0.20
7020L133	200 x 1330	1060 – 1113	48	0.21
7020L137	200 x 1370	1029 – 1080	49	0.21
7020L141	200 x 1410	1000 – 1050	50	0.22
7020L145	200 x 1450	972 – 1020	52	0.23
7020L149	200 x 1490	946 – 993	53	0.23
7020L153	200 x 1530	921 – 967	55	0.24
7020L157	200 x 1570	897 – 942	56	0.24
7020L161	200 x 1610	875 – 918	58	0.25
7020L165	200 x 1650	853 – 896	59	0.26
7020L169	200 x 1690	833 – 875	60	0.26
7020L173	200 x 1730	814 – 854	62	0.27
7020L177	200 x 1770	795 – 835	63	0.28
7020L181	200 x 1810	777 – 816	65	0.28

200mm Mirror Demister Sizes and Technical Information

Product code	Size (mm)	Resistance range (Ohms)	Power (Wattage)	Current (Amps)
7020L185	200 X 1850	761 – 799	66	0.29
7020L189	200 X 1890	744 – 782	68	0.29
7020L193	200 X 1930	729 – 765	69	0.30
7020L197	200 X 1970	714 – 750	71	0.31
7020L201	200 X 2010	700 – 735	72	0.31
7020L205	200 X 2050	686 – 720	73	0.32
7020L209	200 X 2090	673 – 706	75	0.33
7020L213	200 X 2130	660 – 693	76	0.33
7020L217	200 X 2170	648 – 680	78	0.34
7020L221	200 X 2210	636 – 668	79	0.34
7020L225	200 X 2250	625 – 656	81	0.35
7020L229	200 X 2290	614 – 644	82	0.36
7020L233	200 X 2330	603 – 633	84	0.36
7020L237	200 X 2370	593 – 623	85	0.37
7020L241	200 X 2410	583 – 612	86	0.38
7020L245	200 X 2450	574 – 602	88	0.38
7020L249	200 X 2490	564 – 593	89	0.39

Specification:

Approved to: EN60335-1:2002+A1, A2, A11, A12, A13, A14, A15 and EN60335-2-30:2009+A11

Power Rating: 200W/m² | **Standard Voltage:** 230V

Insulation Class: 2-double insulated | **Thickness:** 1 mm

IP Rating: 44

Warranty: Lifetime warranty

Cable connector: 30 x 40 x 5mm | **Cable:** 1m twin core 0.75mm² oval

Adhesive: Acrylic | **Material:** Double insulated multi-layer polyester/polyethylene

Mirror temperature: Approximately 15°C above ambient room temperature

Heating time: 3-5 Minutes depending on ambient room temperature

Heat spread: Approximately 30% area around the pad



Over 400 different sizes available including 12V SELV, 24V and 110V versions

Call our technical support team on 01444 247020 for further information or installation advice:

tech@heatmat.co.uk | www.heatmat.co.uk